

EC type examination certificate
EG-Baumusterprüfbescheinigung

CE-0085CR0393

Product Identification No.
 Produkt-Identnummer


Field of Application <i>Anwendungsbereich</i>	EC Gas Appliances Directive (2009/142/EC) <i>EG-Gasgeräterichtlinie (2009/142/EG)</i>
Distributor <i>Vertreiber</i>	CHAFFOTEAUX SAS Le Carré Pleyel, 5 rue Pleyel, F-93521 St. Denis - Cedex
Product Category <i>Produktart</i>	Boilers with flue systems: Condensing water heater (3202)
Product Description <i>Produktbezeichnung</i>	Condensing combi water heater with closed combustion chamber
Model <i>Modell</i>	PIGMA ...
Countries of Destination <i>Bestimmungsländer</i>	AL, AT, BE, BG, CH, CN, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, TR
Test Reports <i>Prüfberichte</i>	supplement test: K 1936 2017 E9 from 23.11.2017 (TRG) supplement test: K 1936 2017 B10 from 23.11.2017 (TRG)
Test Basis <i>Prüfgrundlagen</i>	2009/142/EG (30.11.2009) DIN EN 15502-1 (01.10.2015) DIN EN 15502-2-1 (01.09.2017)
File Number <i>Aktenzeichen</i>	17-0859-GER

70028-04-A-DE



05.01.2018 Rie B-1/2

Date, Issued by, Sheet, Head of Certification Body
 Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EC Directive

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EG-Richtlinie 2009/142/EG.



Deutsche
 Akkreditierungsstelle
 D-ZE-16028-01-01

DVGW CERT GmbH
 Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
 53123 Bonn

Tel. +49 228 91 88 - 888
 Fax +49 228 91 88 - 993

www.dvgw-cert.com
 info@dvgw-cert.com

Elektrical Data 230 V AC, 50 Hz
Elektrische Daten

Appliance Categories <i>Geräteategorien</i>	Supply Pressures <i>Versorgungsdrücke</i>	Countries of Destination <i>Bestimmungsländer</i>	Remarks <i>Bemerkungen</i>
I2E	20 mbar	DE, LU	
I2E(S)	20/25 mbar	BE	
I2H	20 mbar	AT, DK, EE, FI, LV, NL, NO, SE	
I2L	20/25 mbar	NL	
I3P	28-30 mbar	CY	
II2E LwLs3P	20,20,13, 30 mbar	PL	
II2E(S)3P	20/25, 37 mbar	BE	
II2Esi3P	20/25, 37 mbar	FR	
II2H3P	20, 30 mbar	LT	
II2H3P	20, 37 mbar	CH, CZ, ES, GB, GR, HR, IE, IS, PT, RO, SI, SK, TR	
II2HM3P	20, 37 mbar	IT	
II2HS3P	20, 37 mbar	HU	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
Pigma GREEN ULTRA IN 25 X R&D	sanitary water heat input (Hi): 3,7...26,0 kW nominal heat output: 3,4...21,4 kW heat input (Hi): 3,7...22,0 kW	serial numbers: 007, 008, 009, 010, 011; only for IT
PIGMA ADVANCE 18	nominal heat output: 3,4...17,6 kW heat input (Hi): 3,7...18,0 kW	
PIGMA ADVANCE 24	sanitary water heat input (Hi): 3,7...26,0 kW nominal heat output: 3,4...21,4 kW heat input (Hi): 3,7...22,0 kW	
PIGMA ADVANCE 30; PIGMA ADVANCE L 30	sanitary water heat input (Hi): 4,3...30,0 kW nominal heat output: 3,9...27,4 kW heat input (Hi): 4,3...28,0 kW	
PIGMA ADVANCE 35	sanitary water heat input (Hi): 5,0...34,5 kW nominal heat output: 4,7...30, kW heat input (Hi): 5,0...31,0 kW	

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

flue types: B23, B23P, B33, C13(x), C23, C33(x), C43(x), C53(x), C63(x), C83(x) and C93(x) according to installation manual with flue systems of Centrotec (approval no. 0036 CPR 9169 003), Muelink & Grol (approval no. 0432-BPR-220556), Skoberne (approval no. 0036 CPD 9184 001-2007), Groppalli (approval no. 0694-CPR-7968) and LN Natalini (approval no. 0694-CPR-8045).

Additional proved countries of destination, appliance categories and supply pressures:

BG: II2H3P (20, 30 mbar)

CN, CY: I2H (20 mbar)

AL, MK, MT, RS: II2H3P (20, 37 mbar)

In Albania, China, Macedonia and in Serbia the CE-marking will be accepted as conformity approval if the Gas Appliance Directive (2009/142/EC) is transferred into national law by Albania, China, Macedonia and Serbia.



EC type examination certificate
EG-Baumusterprüfbescheinigung


CE-0085CR0393
 Product Identification No.
 Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EC Efficiency Directive (92/42/EEC) <i>EG-Wirkungsgradrichtlinie (92/42/EWG)</i>
Distributor <i>Vertreiber</i>	CHAFFOTEAUX SAS Le Carré Pleyel, 5 rue Pleyel, F-93521 St. Denis - Cedex
Product Category <i>Produktart</i>	Boilers with flue systems: Condensing water heater (3202)
Product Description <i>Produktbezeichnung</i>	Condensing combi water heater with closed combustion chamber
Model <i>Modell</i>	PIGMA ...
Type of Boiler <i>Heizkesseltyp</i>	condensing boiler
Test Reports <i>Prüfberichte</i>	supplement test: K 1936 2017 B11 from 23.11.2017 (TRG)
Test Basis <i>Prüfgrundlagen</i>	EU/92/42 (21.05.1992)
File Number <i>Aktenzeichen</i>	17-0859-GWR

70028-04-A-CE



05.01.2018 Rie B-1/2



Date, Issued by, Sheet, Head of Certification Body
 Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of heating boilers under EC Directive 92/42/EC.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Heizkesseln nach der Richtlinie 92/42/EWG.



DVGW CERT GmbH
 Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
 53123 Bonn

Tel. +49 228 91 88 - 888
 Fax +49 228 91 88 - 993

www.dvgw-cert.com
 info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Energy Labelling Energieeffizienzkennzeichnung
PIGMA ADVANCE 18	nominal heat output: 3,4...17,6 kW heat input (Hi): 3,7...18,0 kW	
PIGMA ADVANCE 24	sanitary water heat input (Hi): 3,7...26,0 kW nominal heat output: 3,4...21,4 kW heat input (Hi): 3,7...22,0 kW	
PIGMA ADVANCE 30; PIGMA ADVANCE L 30	sanitary water heat input (Hi): 4,3...30,0 kW nominal heat output: 3,9...27,4 kW heat input (Hi): 4,3...28,0 kW	
PIGMA ADVANCE 35	sanitary water heat input (Hi): 5,0...34,5 kW nominal heat output: 4,7...30, kW heat input (Hi): 5,0...31,0 kW	